

# PERMA-SEAL-3-PORT VALVE

MADE IN  
NORTH AMERICA



PRODUCTS

Size:	1 1/2" - 2" - 2 1/2" spigot
Material:	CPVC body black , Glass filled Noryl rotor, ABS handle, NSF 61
O-RINGS:	EPDM
Rotor Seal:	High temperature silicone gasket with teflon jacket
Pressure Rating:	50 psi
Positive seal back pressure:	15 psi
Vacuum Rating:	29" Mercury

PRIVATE LOGO AVAILABLE (size: 7/16" 1 3/4")  
FIRST GLANCE TWO COLOUR FLOW INDICATOR MARKINGS  
"OPEN-CLOSED-FLOW DIRECTIONS"



## FEATURES:

- Proportional mixing availability.
- Double O-ring shaft seal.
- Permanently lubricated rotor seal with extreme wear resistance, exceeds 3000 dry cycle requirement.
- Chlorine, acid and ozone resistant construction.
- Handle-locking knob provides eye-let for lock attachment.
- Engineered "PLAST-TITE" screws ( 18.8 stainless ) will not crack plastic when servicing valve.
- Universal shaft spline pattern adapts to most actuators.
- All wetted materials are of NSF-50 or 61 designation.
- **PATENTED DESIGN US 6497250**

## CPVC BODY



NOTE: VISIT [www.nsf.org](http://www.nsf.org) FOR UPDATED LISTINGS

OV2-2010

PART #	DESCRIPTION	LIST PRICE	QTY. PER CARTON
OV3 - 2000	2"- 2 1/2" 3 PORT VALVE (UPVC) C/W 3 X 1 1/2" BUSHINGS	\$56.00	12
OV3 - 2010	2" - 2 1/2" 3 PORT VALVE (UPVC) SOCKET	\$50.00	12
OV3 - 1500	1 1/2" - 2" 3 PORT VALVE (UPVC) SOCKET	\$50.00	12
OV3 - 1503	1 1/2" 3 PORT VALVE - 1 1/2" FIP THREADED NPT	\$50.00	12
VF2-2010	2" - 2 PORT WITH FLOW INDICATOR HANDLE	\$44.00	12
OV2 - 2090	2"-2 1/2" 2 PORT VALVE 90° SOCKET	\$44.00	12
OV2 - 1590	1 1/2"-2" 2 PORT VALVE 90° SOCKET	\$44.00	12
OV2 - 2000	2"-2 1/2" 2 PORT VALVE SKT, C/W BUSHINGS	\$48.00	12
OV2 - 2010	2"-2 1/2" 2 PORT VALVE, SOCKET	\$44.00	12
OV2 - 1500	1 1/2"-2" 2 PORT VALVE, SOCKET	\$44.00	12