

BIG KAHUNA 3" PVC, 3 PORT ROTARY DIVERTER VALVE

MADE IN NORTH AMERICA



Size:	2.5" socket—3" spigot
Material:	Body, cover, nut, NSF approved PVC-grey
Rotor:	NSF approved glass reinforced Polyphenylene oxide
O-rings:	NSF approved EPDM
Rotor seal:	NSF approved low friction ethylene elastomer
Rotor load bearings:	NSF approved low friction polyoxymethylene
Pressure rating:	50 psi with full seal back pressure rating
Vacuum rating:	29 inch mercury Burst pressure: 500 psi
Flow rating:	400 GPM @ 4.4 psi head loss



FEATURES:

- Easy read valve position indicator
- Low friction elastomeric seal with full vacuum rating
- High strength diverter with precision machined load bearings
- Easy valve servicing with spin off union nut—no special tools required
- Double shaft seal O-rings
- Patented rotor seal de-energizing chamber for “off service position”
- Patented internal “ANTI SEAL PINCH” design
- Electric Actuator package 24VAC or 110VAC – (600 inch pounds torque, amps drawn for 24VAC = 2.6, 110VAC = 1.0)
- Easy actuator retrofitting
- Multiple (4) indexing positions for common port selection
- Made in North America (Canada)

PART #	DESCRIPTION	LIST PRICE	QTY. PER CTN.
OV3 - 3000	3 SPGT PVC DIVERTER VALVE	\$300.00	1
LCR-24-600	3" PVC 3-PORT VALVE WITH 24V ACTUATOR	\$1320.00	1
LCR-110-600	3" PVC 3-PORT VALVE WITH 110V ACTUATOR	\$1320.00	1