

# MANUAL BUTTERFLY VALVES S4

MADE IN  
NORTH AMERICA



PRODUCTS

Size:	3" to 8"
Material:	PVC, PP
O-RINGS:	EPDM/Viton
Pressure Rating:	150 P.S.I at 73°F up to 4"
	95 P.S.I at 73°F 6"-8"



**FLANGE O-RING DOES NOT REQUIRE  
FLANGE GASKETS!**

## FEATURES:

- Double lip "SUPER" seal
- Space-saving design
- Increased disc stiffness due to proprietary glass filled plastic core (reinforced noryl)
- Bubble-tight shutoff
- Excellent throttling characteristics
- Retrofitted to accommodate optional actuators
- Flange bolt holes accommodate ISO, DIN, ASA bolt circles
- Dynamically sealed, no liner necessary
- Increased flow due to larger than standard bore
- Also available with electric and pneumatic actuators (see pg. 20)

## SUGGESTED APPLICATIONS

- Water treatment
- Swimming pools & filtration
- Waste water treatment
- Slurries
- Irrigation systems
- Secondary oil recovery
- Chilled water
- Golf courses
- Sea water
- Tank trucks
- Sewage systems
- Chemical media

PVC HAND LEVER OPERATED				
	EPDM Seats		Viton Seats	
SIZE	MODEL #	LIST PRICE	MODEL #	LIST PRICE
3"	11-300	\$307.00	11-301	\$527.16
4"	11-400	\$323.00	11-401	\$552.00
6"	11-600	\$470.00	11-601	\$652.80
8"	11-800	\$591.00	11-801	\$1028.40



**NEW**

PVC FLANGE KITS FOR PRAHER BUTTERFLY VALVES ( INCLUDING HARDWARE)				
PIPE SIZE	BOLT SIZE/LENGTH	REQUIRED/VALVE	PART #	LIST PRICE
3"	5/8 X 5"	4	F10-300	\$180.00
4"	5/8 X 5"	8	F10-400	\$228.00
6"	3/4 X 6.5"	8	F10-600	\$380.00
8"	3/4 X 6.5"	8	F10-800	\$519.00

for dimensions see page 74

Grade 5 steel bolt zinc plated with hex nut and two flat washers

Recommended Torque rating for flanges: 3 - 4" 25ft. lbs., 6 - 8" 40ft.lbs

FULL FACE EPDM FLANGE GASKET ( 150 LBS)		
PIPE SIZE	PART #	LIST PRICE
3"	F103 001 25EPG	\$13.88
4"	F104 001 25EPG	\$17.35
6"	F106 001 25EPG	\$27.76
8"	F108 001 25EPG	\$50.00